



AMS 3011 – Mini Pressure Transmitter with 0 .. 5 V Output

Übersicht

Die streichholzschaftelgroßen Drucktransmitter der Serie AMS 3011 mit 0 .. 5 V Spannungsausgang haben ein robustes, staub- und wasserdichtes (IP67) Metallgehäuse. Die Druckanschlüsse der AMS 3011 sind als M5 Innengewinde ausgeführt und der elektrische Anschluss als M5 Einbaustecker. Die Mini-Transmitter eignen sich besonders für differentielle Druckmessungen mit hohem Systemdruck im Innen- und Außenbereich. Die AMS 3011 können mit einer Versorgungsspannung von 8 ... 36 V betrieben werden.

Alle AMS 3011 sind kalibriert und in einem Temperaturbereich von -25 ... 85 °C temperaturkompensiert. Damit wird eine hohe Genauigkeit bei Raumtemperatur und ein geringer Gesamtfehler über den gesamten Temperaturbereich erreicht.

Verfügbare Druckbereiche

- Differentieller (relativer) Druck:
0 ... 50 mbar bis zu 0 ... 10 bar
- Bidirektional differentieller Druck:
-25 ... +25 mbar bis zu -1 ... +1 bar
- Absolutdruck:
0 ... 1 bar und 0 ... 2 bar
- Barometrischer Druck:
700 ... 1200 mbar

Kundenspezifische Druckbereiche und Modifikationen sind auf Anfrage erhältlich.

Typische Anwendungen

- Industrielle Prozesskontrolle
- Medizinischer Apparatebau
- Vakuumüberwachung
- Füllstandsmessung
- Pneumatische Systemüberwachung
- Prüfstände

Overview

AMS 3011 is a series of matchbox sized pressure transmitters with 0 .. 5 V voltage output in a robust dust- and water-tight (IP67) metal package. AMS 3011's pressure ports are realized by two M5 female threads and the electrical connection by M5 circular sensor connector. The mini transmitters are especially suitable for differential pressure measurement with large common-mode pressure in indoor and outdoor applications. The AMS 3011 can be powered within a wide supply voltage range of 8 .. 36 V.

All AMS 3011 are calibrated and temperature compensated in a range of -25 .. 85 °C and feature high accuracy at room temperature as well as a low overall error throughout the entire compensated temperature range.

Available Pressure Ranges

- Differential (relative) pressure:
0 .. 50 mbar up to 0 .. 10 bar
- Bidirectional differential pressure:
-25 .. +25 mbar up to -1 .. +1 bar
- Absolut pressure:
0 .. 1 bar and 0 .. 2 bar
- Barometric pressure:
700 .. 1200 mbar

Custom specific pressure ranges or modifications are available on request.

Typical Applications

- Industrial process control
- Medical instrumentation
- Vacuum monitoring
- Level measurement
- Pneumatic system monitoring
- Test benches

analog microelectronics

Analog Microelectronics GmbH
An der Fahrt 13, D – 55124 Mainz

Phone: +49 (0)6131/91 073-0
Fax: +49 (0)6131/91 073-30
Internet: www.analogmicro.de
E-Mail: info@analogmicro.de

May 2017

AMS 3011 – Mini Pressure Transmitter with 0 .. 5 V Output

Short Specifications

Excerpt from AMS 3011's datasheet, all parameters apply to $V_S = 24.0 \text{ V}$ and $T_{op} = 25 \text{ }^\circ\text{C}$

Parameter	Minimum	Typical	Maximum	Units
Analog output signal (non-ratiometric)				
@ specified minimum pressure	0	< 0.025	0.05	V
@ specified maximum pressure		5		V
Full span output (FSO)		5		V
without pressure (bidirectional differential)		2.5		V
Accuracy @ $T = 25 \text{ }^\circ\text{C}$ (acc. EN 61298)				
Low pressure sensors (50, 100 mbar)		± 0.5	± 1.0	%FSO
Standard and medium pressure sensors ($\geq 200 \text{ mbar}$)		± 0.5	± 1.0	%FSO
Overall error (pressure meas.) @ $T = -25 \dots 85 \text{ }^\circ\text{C}$				
Low pressure sensors (50, 100 mbar)		± 1.0	± 2.0	%FSO
Standard pressure sensors ($\geq 200 \text{ mbar}$)		± 0.7	± 1.5	%FSO
Long term stability			< 0.5	%FSO/a
Resolution A/D converter		14		Bits
Resolution analog output signal			0.05	%FSO
Nonlinearity (included in accuracy)	-0.3	< 0.1	0.3	%FSO
Supply voltage (V_S)	8	24	36	V
Current consumption			5	mA
Reaction time (10 % .. 90 % rise time)		1	2	ms
Common mode pressure			16	bar
Package material	Hard-eloxed aluminum			
Weight		45		g
Dimensions without connector ($L \times W \times H$)		35 x 25 x 25		mm

Weitere Informationen:

<http://www.analogmicro.de/de/products/sensors/pressuretransmitter/ams3011/> (Deutsch)



Further information:

<http://www.analogmicro.de/en/products/sensors/pressuretransmitter/ams3011/> (English)

